



FAST-TRAK®

Walk-In Coolers and Freezers

**Easy installation with the flexibility
of additional options**


Features

- Available in widths of: 4', 5', 6', 7', 8', 9', 10', 11' and 12'
- Depths of 6', 7', 8', 9', 10', 11', 12' and 14'
- Heights: 6'7", 7'7" & 8'7" with floor, 7'4" and 8'4" floorless
- Indoor or outdoor models
- Coolers, freezers or combination cooler/freezers
- Fast and easy installation
- Exterior finish is corrosion resistant stucco embossed coated steel
- Full 4" panel foamed-in-place with HFC free
- HFO polyurethane insulation
- 30" or 36" self-closing door
- Digital thermometer and light switch
- Adjustable spring loaded hinge
- Spring actuated door closer
- Deadbolt locking handle for security
- Refrigeration system choices include remote Split-Pak™ and self-contained Capsule Pak ECO™ (available on single compartment walk-ins under 14' in length)
- Temperatures: +38°F, +37°F, -10°F
- 15 year panel warranty



OPTIONS


- Aluminum diamond tread or stainless steel interior and exterior kickplates
- With floor/less floor combination*
- Exterior ramp (with floor models)
- Interior ramp*
- Non-skid strips (shipped loose)
- Extra vapor-proof lights (shipped loose)
- Additional LED lighting
- Outdoor membrane roof systems
- Viewports (freezer ports heated)
- Strip curtains (shipped loose)
- Door rain hoods
- Specially designed shelving kits
 - Flexible shelf adjustment in 1" increments
 - Shelving layouts utilize maximum space for storage leaving the door opening clear of end standards
 - Green Kote™ special epoxy-coated finish provides extra protection from acidic foods
 - Quick and easy assembly
 - Rigid construction
 - Optional U-shaped systems



Viewports allow visibility of products stored inside.



Roll items directly into your walk-in with interior ramps*.



Highly efficient LED lighting options fully illuminate your walk-in.

*Consult factory for lead time on this option.

REFRIGERATION SYSTEM OPTIONS

R290
REFRIGERANT



PATENTED
TECHNOLOGY
U.S. Patent No.
11,859,885

CAPSULE PAK ECO™
SELF-CONTAINED SYSTEMS
INDOOR & OUTDOOR MODELS*



A2L
REFRIGERANT

CAPSULE PAK™ REMOTE*
INDOOR & OUTDOOR
Quick-connect systems up to 2 HP



A2L
REFRIGERANT

SPLIT-PAK™
REMOTE SYSTEMS
INDOOR & OUTDOOR MODELS**

* Capsule Pak ECO and Capsule Pak Remote systems are intended for single compartments 14' long and under.

** Dedicated medium temp condensing units meet the DOE requirement of a minimum AWEF rating of 5.61 (Btu/W-h) for indoor models and 7.6 for outdoor models.



891 County Road U • Hudson, WI 54016
800-955-5253 • www.norlake.com

